

# ICAR-NATIONAL BUREAU OF FISH GENETIC RESOURCES

Canal Ring Road, P.O. Dilkusha, Lucknow-226 002, U.P., India Ph. : (0522) 2441735, 2440145, 2442440, 2442441 Fax : (0522) 2442403 : Website : <u>www.nbfgr.res.in</u>



F.No. 3 (120)/Aluminum Partition in Museum/2018-19/(Store)/

Dated: 28/01/2019

## **NOTICE INVITING TENDER THROUGH E-PROCUREMENT**

Online Bids are invited from the interested firms under two bid system for procurement of "**Aluminum Partition in Museum with complete installation**" at ICAR-National Bureau of Fish Genetic Resources, Canal Ring Road, Telibagh, P.O. Dilkusha, Lucknow-226002. <u>Manual bids shall not be entertained.</u>

Tender documents may be downloaded from e-procurement website of CPP <u>http://eprocurement.gov.in/eprocurement/app</u> as per the schedule as given in CRITICAL DATE SHEET as under.

## CRITICAL DATE SHEET

Tender No.	F.No. 3(120)/2018-19/Store/
Date and Time for Issue/Publishing	05:30 PM on 28/01/2019
Document Download/Sale Start Date and Time	05:30 PM on 28/01/2019
Bid Submission Start Date and Time	06:00 PM on 28/01/2019
Bid Submission End Date and Time	02:00 PM on 06/02/2019
Date and Time for Opening of Bids	02:00 PM on 07/02/2019
Address for Communication	Asstt. Administrative Officer (S&P)
	ICAR- National Bureau of Fish Genetic
	Resources, Canal Ring Road, Telibagh, P. O.
	Dilkusha, Lucknow-226002

Asstt. Administrative Officer

## Annexure-I

## **INSTRUCTIONS FOR ONLINE BID SUBMISSION**

- 1. The tender from/bidder documents may be downloaded from the website: <u>http://eprocurement.gov.in/eprocurement/app</u>. Online submission of Bids through Central Public Procurement Portal (<u>http://eprocure.gov.in/eprocure/app</u>) is mandatory. Manual/Offline bids shall not be accepted under any circumstance.
- 2. Tenders/bidders are requested to visit website: <u>http://eprocure.gov.in/eprocure/app</u> regularly. Any changes/modifications in tender enquiry will be intimated by corrigendum through this website only.
- 3. In case, any holiday is declared by the Government on the day of opening, the tenders will be opened on the next working day at the same time. The council reserves the right to accept or reject any or all the tenders.
- 4. The interested firms are required to deposit (in original) Earnest Money Deposit (EMD) worth <u>Rs.</u> <u>30,000/- (Rupees Thirty Thousand Only)</u> in the form of Demand Draft/Bank Guaranty from any of the Commercial Bank in favour of ICAR Unit: NBFGR, payable at Lucknow may be addressed to the Administrative Officer, National Bureau of Fish Genetic Resources, Canal Ring Road, Telibagh, P.O. Dilkusha, Lucknow-226002 on or before bid opening date and time as mentioned in the Critical Date Sheet.
- 5. The firm should send the Original brochures of the product and may be addressed to the Asstt. Administrative Officer, National Bureau of Fish Genetic Resources, Canal Ring Road, Telibagh, P.O. Dilkusha, Lucknow-226002 on or before bid opening date and time as mentioned in the Critical Date Sheet.
- 6. Bidder need not to come at the time of Technical as well as Financial bid opening at ICAR-NBFGR. They can view live bid opening after login on CPP e-procurement Portal at their remote end. If bidder wants to join bid opening event at ICAR-NBFGR then they have to come with bid acknowledge slip that generates after successful submission of online bid.

## The firms are also required to upload copies of the following documents:-

## • Technical:

- (a) Scanned copy of Earnest Money Deposit (EMD/its exemption, if any.
- (b) Scanned copy of Firm's registration, Pan Card, GSTIN No., Tender Acceptance Letter (Annexure-IV).
- (c) Scanned copy of Manufacturers Authorization Certificate issued by Principal Manufacture duly verified by the Indian Agent or Manufacturing Certificate.
- (d) Scanned copy of Income Tax Statement for the last three years.
- (e) Scanned copy of Annexure-II and III.
- (f) Scanned copy of Make and Model of all systems, sub systems and additional items should be mentioned in the technical bid and complete technical details should be provided in the form of Brochures and write-ups.

## Note:

<u>Circular No. 1(2)(1)/2016-MA dated 10<sup>th</sup> March 2016</u> of Ministry of Micro, Small & Medium Enterprises (MSE,s) and <u>Circular No. F/20/2/2014-PPD (Pt)</u>, dt.26/07/2016 of Ministry of Finance, Department of Expenditure, Procurement Policy Division; regarding relaxation of Norms for Startups and Micro & Small Enterprises in Public Procurement on Prior Experience-Prior Turnover Criteria prior turnover would be applicable.

## • Financial Bid:

- (a) Price Bid as BoQ .....
- \* Item should be of reputed make and suitable for high end elite users.
- \* Submission of samples of the quoted items is compulsory without which the rates will not be considered. Rates will be opened only for those items for which the samples is approved with respect to the requirement.
- \* Tax extra as applicable should be indicated separately in the column provided.

**Note:**- The above mentioned Financial Proposal/Commercial Bid format is provided as BoQ\_XXXX. xls along with this tender document at (<u>http://eprocure.gov.in/eprocure/app</u>. Bidders are advised to download this BoQ\_XXXX. xls as it is and quote their offer/rates in the permitted column and upload the same in the Financial Bid. Bidder shall not tamper /modify downloaded price bid template in any manner. In case if the same is found to be tempered/modified in any manner, tender will be completely rejected and EMD would be forfeited and tenderer is liable to be banned from doing business with ICAR-NBFGR.

Asstt. Administrative Officer

## Annexure-II

## **Terms & Conditions**

- 1. The tender shall quote rates, which will include the delivery and other incidental charges, Taxes, if any, should be indicated separately.
- 2. The rates should be quoted as per the BOQ uploaded on the CPP Portal. Taxes, if any, should be indicated separately. If must be noted that the contract shall be awarded to the firm which fulfils all the required terms and conditions and remains L-1 for any particular items.
- 3. The firm must also possess valid PAN No., GSTIN No. and a copy of the same must also be enclose with the tender document.
- 4. Copy of previous three years of Income Tax Statement may be furnished.
- 5. Modification in the tender documents after the closing date is not permissible.
- 6. The successful firm shall have to supply the Various Scientific Equipments within 6 weeks from the date of confirmed supply order and if the materials are not supplied in time then EMD/Security shall be forfeited. The rates quoted shall be valid for one year from the date of opening of tender.
- 7. The contractor/bidder or his representative may contact the undersigned at Telephone No. 0522-2441735, 2440145 for any further clarification No. variation in terms of quality of the terms shall be entertained or else EMD/Security Deposit shall be forfeited.
- 8. The Director, ICAR-National Bureau of Fish Genetic Resources (ICAR-NBFGR) shall have the right to reject all or any of the offers, accept more than one offer, and assign part of the job.
- 9. Merely quoting of lowest rates does not mean that order shall be given to that firm. The Competent Authority will finally decide on the basis of quality and performance of past installation.
- 10. The interested firms are required to deposit (in original) an Earnest Money Deposit (EMD) of the amount worth **Rs. 30,000/- (Rupees Thirty Thousand Only)** in the form of Demand Draft/Bank Guaranty from any of the Commercial Bank in favour of **ICAR Unit: NBFGR, payable at Lucknow may be addressed to the Administrative Officer, National Bureau of Fish Genetic Resources, Canal Ring Road, Telibagh, P.O. Dilkusha, Lucknow-226002. No tender shall be considered without the Earnest Money Deposit. Demand Draft other than drawn in favour of any officer "ICAR Unit-NBFGR payable at Lucknow will not be accepted and the tender will be rejected. The Earnest Money will be refunded only after the finalization of the procurement and no interest will be paid on Earnest Money.**
- 11. Rates once finalized will not be enhanced/reduced during the currency of the contract.
- 12. In case of foreign currency, conversion rates in INR will be taken on that day when financial bid will open.
- 13. In case, the successful bidder shows inability at any stage, after the contract is finalized and awarded, for whatsoever reason (s), to honour the contract, the Earnest Money/ Performance Security deposited would be forfeited.
- 14. The Director, ICAR-NBFGR reserves the right to cancel the contract at any time during the currency period of the contract without giving any reason.

- 15. The firm to whom the tender will be awarded, will have to deposit the Performance Security equal to 10% of the total amount at the time of installation of the equipment. If the services are not found to be satisfactory, the Performance Security is liable to be forfeited. No. interest will be paid on Performance Security.
- 16. If any disputes (s) arises between ICAR-NBFGR and the firm with reference to the contract, ICAR-NBFGR will decide it and its decision will be binding on the firm.

## 17. Bid Validity: 180 days.

- 18. The contract will be given to item-wise Least one (L-1).
- 19. Our Institute is Registered with DSIR and we are exempted from Excise Duty & Custom Duty. Hence CDEC/DSIR will be provided to the firm, if demanded. Rate should be quoted accordingly.

## 20. **PAYMENT:**

- (A) Payment for Goods supplied from abroad:
  - (a) On shipment 90% of the contract price (FOB) shall be paid through irrevocable Letter of Credit upon submission of documents detailed in L/C.
  - (b) 10% of the contract price (FOB) (in foreign currency) and other charges like freight etc. from FOB to FOR ICAR-NBFGR, Lucknow (in INR) will be released after satisfactory installation/working of equipment/machine etc. As well as on submission/production of Performance Bank Guarantee by the supplier (s).
- (B) Payment for Goods supplied within India:
  - (a) 100% of the contract price on receipt of goods by the consignee supported by satisfactory installation/working report and submission of PBG.

## 21. **INSTALLATION:**

Within 30 days from the date of receipt of equipment in the Institute failing which liquidated Damage clause shall apply.

**Liquidated Damage Clause:** It would be realized @0.5% (half per cent) of the base price (excluding taxes) of the delayed goods for each week of delay subject to maximum 10%.

## 22. **Price:**

- i. If any bidder wants to quote in foreign currency, price be quoted on FOB international port of shipment in foreign currency and all charges from FOB international Port to FOR, ICAR-NBFGR, Lucknow (like: Air/Sea freight, insurance, custom duty against CDEC, Custom Clearing charges and transportation up to ICAR-NBFGR, Lucknow) should be quoted in INR only.
- ii- If any bidder wants to quote in INR, Price be quoted on FOR, ICAR-NBFGR, Lucknow basis.
- iii- IN CASE THE STORES PERTAINS TO IMPORT:
- (a) KINDLY ENSURE TO ENCLOSE MANUFACTURER'S AUTHORIZATION IN FAVOUR OF INDIAN SUBSIDIARY FIRM. IT MAY ALSO BE NOTED THAT FURTHER AUTHORIZATION BY SUBSIDIARY FIRM IN FAVOUR OF ANY OTHER FIRM LOCATED IN INDIA TO PROMOTE THEIR SALE MUST HAVE AUTHORIZATION FROM THE PRINCIPAL FIRM FOR FURTHER AUTHORIZATION TO AN INDIAN FIRM, FAILING WHICH THE TENDER IS LIABLE TO BE CANCELLED.

- PRICE SHOULD BE QUOTED ON FOR INTERNATIONAL AIRPORT/ SEAPORT AND (b) CIF NEW DELHI ALSO. IN CASE ANY FIRM QUOTES THE RATE ON FCA EX-WORKS BASIS ONLY, FCA OR EX-WORKS PRICE WILL BE TREATED AS FOR INTERNATIONAL AIRPORT/ SEAPORT.
- PRICE CAN ALSO BE QUOTED IN INR (FOR BASIS), BUT IN THAT CASE EITHER (c) CDEC/DSIR OR GST CAN BE DEMANDED DEMAND FOR BOTH GST AND CDEC/DSIR CAN NOT BE CONSIDERED.
- (d) PRICE SHOULD BE QUOTED FROM FOB TO FOR DESTINATION (ICAR-NBFGR) IN INDIAN CURRENCY (INR) ALSO.

"Terms and conditions are acceptable"

Dated:

(Authorized Signatory of the firm)

7

# Annexure-III

**ICAR-NATIONAL BUREAU OF FISH GENETIC RESOURCES** 

Canal Ring Road, P.O. Dilkusha, Lucknow-226 002, U.P., India Ph. : (0522) 2441735, 2440145, 2442440, 2442441 Fax : (0522) 2442403 : Website : <u>www.nbfgr.res.in</u>

Name of the firm

Registered/Postal Address :

:

1.	Permanent Account Number	
	(PAN No.)	
2.	GST Registration No., if	
	applicable	
3.	Bank Details:	
a	Bank Name	
b	Branch Address	
С	Account No.	
d	Type of Account (Current/Saving)	
e	MICR No.	
f	RTGS/NEFT Code:	

Date:

Name of the Authorized Signatory

Place:



Stamp & Signature

## **Annexure-IV**

TENDER ACCEPTANCE LETTER
(to be given on Company Letter Head)

Date:

To,	
Sub:	Acceptance of terms and conditions of tender:
Tende	r Reference No.:
	of tender/work:-
Dear S	bir,
1.	I/we have downloaded/obtained the tender document (s) for the above mentioned Tender/work
from t	he website (s) namely:

.....

As per your advertisement, given in the above mentioned website (s).

3. The corrigendum (s) issued from time to time by your department/organization too have also been taken into consideration, while submitting this acceptance letter.

4. I/we hereby unconditionally accept the tender conditions of above mentioned tender document (s)/corrigendum (s) in its totality/entirety.

5. I/we do hereby declare that our firm has not been blacklisted/debarred by any Govt. Department/Public Sector Undertaking.

6. I/we certify that all information furnished by the our firm is true and correct and in the event the information is found to be incorrect/untrue for found violated, then your department/organization shall without giving any notice or reason therefore or summarily reject the bid or terminate the contract, without prejudice to any other rights or remedy including the forfeiture of the full said earnest money deposit absolutely.

Yours faithfully, (Signature of the Bidder, with official seal)

## Annexure-V

## **INSTRUCTION FOR ONLINE BID SUBMISSION**

The bidders are requested to submit soft copies of their bids electronically on the CPP Portal, using valid Digital Signature Certificates. The instructions given below are meant to assist the bidders in registering on the CPP Portal, prepare their bids in accordance with the requirements and submitting their bids online on the CPP Portal.

More information useful for submitting online bids on the CPP Portal may be obtained at: <u>https://eprocure.gov.in/eprocure/app</u>.

#### **REGISTRATION:**

- Bidders are required to enrol on the e-Procurement module of the Central Public Procurement Portal (URL: https://eprocure.gov.in/eprocure/app) by clicking on the link "Online Bidder Enrolment" on the CPP Portal which is free of charge.
- As part of the enrolment process, the bidders will be required to choose a unique username and assign a password for their accounts.
- Bidders are advised to register their valid email address and mobile numbers as part of the registration process. These would be used for any communication from the CPP Portal.
- Upon enrolment, the bidders will be required to register their valid Digital Signature Certificate (Class II or Class III Certificates with signing key usage) issued by any Certifying Authority recognized by CCA India (e.g. Sift / TCS /nCode /eMudhra etc.), with their profile.
- Only one valid DSC should be registered by a bidder. Please note that the bidders are responsible to ensure that they do not lend their DSC's to others which may lead to misuse.
- Bidder then logs in to the site through the secured log-in by entering their user ID/password and the password of the DSC/e-Token.

## SEARCHING FOR TENDER DOCUMENTS:

- There are various search options built in the CPP Portal, to facilitate bidders to search active tenders by several parameters. These parameters could include Tender ID, Organization Name, Location, Date, Value etc. There is also an option of advanced search for tenders, wherein the bidders may combine a number of search parameters such as Organization Name, Form of Contract, Location, Date, other keywords etc. to search for a tender published on the CPP Portal.
- Once the bidders have selected the tenders they are interested in, they may download the required documents / tender schedules. These tenders can be moved to the respective 'My Tenders' folder. This would enable the CPP Portal to intimate the bidders through SMS / e-mail in case there is any corrigendum issued to the tender document.
- The bidder should make a note of the unique Tender ID assigned to each tender, in case they want to obtain any clarification / help from the Helpdesk.

## PREPARATION OF BIDS

• Bidder should take into account any corrigendum published on the tender document before submitting their bids.

- Please go through the tender advertisement and the tender document carefully to understand the documents required to be submitted as part of the bid. Please note the number of covers in which the bid documents have to be submitted, the number of documents including the names and content of each of the document that need to be submitted. Any deviations from these may lead to rejection of the bid.
- Bidder, in advance, should get ready the bid documents to be submitted as indicated in the tender document/schedule and generally, they can be in PDF /XLS /RAR/DWF/JPG formats. Bid documents may be scanned with 100 dpi with black and white option which helps in reducing size of the scanned document.
- To avoid the time and effort required in uploading the same set of standard documents which are required to be submitted as a part of every bid, a provision of uploading such standard documents (e.g. PAN Card Copy, Annual Reports, Auditor Certificates etc.) has been provided to the bidders. Bidders can use "My Space" or "Other Important Documents" area available to them to upload such documents. These documents may be directly submitted from the "My Space" area while submitting a bid, and need not be uploaded again and again. This will lead to a reduction in the time required for bid submission process.

#### SUBMISSION OF BIDS

- Bidder should log into the site well in advance for bid submission so that they can upload the bid in time i.e. on or before the bid submission time. Bidder will be responsible for any delay due to other issues.
- The bidder has to digitally sign and upload the required bid documents one by one as indicated in the tender document.
- Bidder has to select the payment option as "offline" to pay the EMD as applicable and enter details of the instrument.
- Bidder should prepare the EMD as per the instructions specified in the tender document. The original should be posted/couriered/given in person to the concerned official, latest by the last date of bid submission or as specified in the tender documents. The details of the DD/any other accepted instrument, physically sent, should tally with the details available in the scanned copy and the data entered during bid submission time. Otherwise the uploaded bid will be rejected.
- Bidders are requested to note that they should necessarily submit their financial bids in the format provided and no other format is acceptable. If the price bid has been given as a standard BoQ format with the tender document, then the same is to be downloaded and to be filled by all the bidders. Bidders are required to download the BoQ file, open it and complete the while coloured (unprotected) cells with their respective financial quotes and other details (such as name of the bidder). No other cells should be changed. Once the details have been completed, the bidder should save it and submit it online, without changing the filename. If the BoQ file is found to be modified by the bidder, the bid will be rejected.
- The serve time (which is displayed on the bidders' dashboard) will be considered as the standard time for referencing the deadlines for submission of the bids by the bidders, opening of bids etc. The bidders should follow this time during bid submission.
- All the documents being submitted by the bidders would be encrypted using PKI encryption techniques to ensure the secrecy of the data. The data entered cannot be viewed by unauthorized persons until the time of bid opening. The confidentiality of the bids is maintained using the secured Socket Layer 128 bit encryption technology. Data storage encryption of sensitive fields is done. Any bid document that is uploaded to the server is subjected to symmetric encryption using a system generated symmetric key. Further this key is subjected to asymmetric encryption using buyers/bid openers public keys. Overall, the uploaded tender documents become readable only after the tender opening by the authorized bid openers.

- Upon the successful and timely submission of bids (i.e. after Clicking "Freeze Bid Submission" in the portal), the portal will give a successful bid submission message & a bid summary will be displayed with the bid no. and the date & time of submission of the bid with all other relevant details.
- The bid summary has to be printed and kept as an acknowledgement of the submission of the bid. This acknowledgement may be used as an entry pass for any bid opening meetings.

## ASSISTANCE TO BIDDERS

- Any queries relating to the tender document and the terms and conditions contained therein should be addressed to the Tender Inviting Authority for a tender or the relevant contact person indicated in the tender.
- Any queries relating to the process of online bid submission or queries relating to CPP Portal in general may be directed to the 24x7 CPP Portal Helpdesk.

# **SPECIFICATION OF EQUIPMENTS** Technical Specification Compliance Statement Form

# Name of the Equipment :Aluminum Partition in Museum with complete<br/>installationQuantity:As per mentioned below

# Note: <u>Total Price should be quote for all required items as per annexure-VI in</u> <u>BOQ (Price Bid).</u>

(A) Name of the work-Partition work in Germplasm conservation Laboratory(museum hall 3 G F)       To be at NBFGR campus         1.       Providing and fixing aluminium handles, ISI marked, anodised       in H	cered iation any
1.       Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete : 125 mm       in I (Pric         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	<b>-</b> J
(anodic coating not less than grade AC 10 as per IS : 1868)       (Pric         transparent or dyed to required colour or shade, with necessary       each       6         125 mm       each       6         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	e filled
transparent or dyed to required colour or shade, with necessary       each       6         125 mm       each       6         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	BOQ
screws etc. complete :       125 mm       each       6         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	e Bid)
125 mmeach62.Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.6	
2. Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	
ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	
sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	
make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	
of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	
junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	
neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	
straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	
including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	
paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge.	
architectural drawings and the directions of Engineer-in-charge.	
(Glazing, paneling and dash fasteners to be paid for separately):	
For fixed portion	
Anodised aluminium (anodised transparent or dyed to required kg 5	
shade according to IS: 1868, Minimum anodic coating of grade AC 15)	
Powder coated aluminium (minimum thickness of powder coating kg 590	
50 micron): 1868, Minimum anodic coating of grade AC 15)	
For shutters of doors, windows & ventilators including providing	
and fixing hinges/ pivots and making provision for fixing of fittings	
wherever required including the cost of EPDM rubber / neoprene	
gasket required (Fittings shall be paid for separately)	
Anodised aluminium (anodised transparent or dyed to required kg 5	
shade according to IS: 1868, Minimum anodic coating of grade AC	
15)	
Powder coated aluminium (minimum thickness of powder coating Kg 67	
50 micron)	
3. Providing and fixing glazing in aluminium door, window, ventilator	
shutters and partitions etc. with EPDM rubber / neoprene gasket etc.	
complete as per the architectural drawings and the directions of	
engineer-in-charge.(Cost of aluminium snap beading shall be paid in	
basic item):	

<ul> <li>Providing and fixing 10 mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS:12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. Drass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge. Pre-laminated particle board with decorative lamination on both sides</li> <li>Repairing and remaking Armstrong existing false celling including necessary material (fastener, main and runner etc., new tile will be paid extrn as per Item.).</li> <li>Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.</li> <li>Providing and fixing pulley roller set for sliding door (two set) and making good etc. complete.</li> <li>Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC IO as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete : 125 mm</li> <li>Providing and fixing aluminium work for doors, windows, wentilators and partitions with extraded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately): - For fixed portion</li> <li>Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC IS)</li> <li>Powder coated aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC IS)</li> <li>Powder coated aluminium (anodised transparent or dyed to required shade accor</li></ul>				
pressed ince layer or graded wood particle board conforming to IS:12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge.         8           Pre-laminated particle board with decorative lamination on both sides         sqm         24           S.         Repairing and remaking Armstrong existing false celling including necessary material (Fastener, main and runner etc., new tile will be paid extra as per Item).         sqm         32           6.         Providing and fixing 100mm brass locks (best make of approved quality) for aluminum doors including necessary cutting and making good etc. complete.         6         5           7.         Providing and fixing pulley roller set for sliding door (two set etc.)         8         6           (B) Name of the work-Partition work in Cell culture repository(muscum G F) at NBFGR campus         8         6           1.         Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete : 125 mm         6           2.         Providing and fixing aluminium handles, ISI marked, andised (anodic coating not regess at all other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium scretions of engineer-in-charge. (Gl		With float glass panes of 5.50 mm thickness	sqm	85
Is:12823 Grade 1 Type II, in panelling fixed in aluminum doors, windows shutters and partition frames with C.P. brass / stailess steel screws etc. complete as per architectural drawings and directions of engineer-in-charge. Pre-laminated particle board with decorative lamination on both sides       9, 24         5.       Repairing and remaking Armstrong existing false celling including necessary material (Pastener, main and runner etc., new tile will be paid extra as per Item.).       32         6.       Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making 100mm brass locks (best make of approved quality) for aluminium hoors including necessary cutting and making publey roller set for sliding door (two set extra set extr	4.			
windows shutters and partition frames with C.P. brass / stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge. Pre-laminated particle board with decorative lamination on both sides 5. Repairing and remaking Armstrong existing false celling including necessary material (Fastener, main and runner etc. new tile will be paid extra as per Hem.). 6. Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete. 7. Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete : 125 mm 6. Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete : 125 mm 6. Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium smap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately): - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron) 3. Providing and fixing glazing in aluminium door, window, venti				
steel screws etc. complete as per architectural drawings and directions of engineer-in-charge. Pre-laminated particle board with decorative lamination on both sides Segm 24 Segm 24 Segm 24 Segm 32 Segm 32				
directions of engineer-in-charge.       sqm       24         Pre-laminated particle board with decorative lamination on both sides       sqm       24         5.       Repairing and remaking Armstrong existing false celling including mecessary material (Fastener, main and runner etc., new tile will be paid extra as per Item.).       sqm       32         6.       Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.       ach       3         7.       Providing and fixing aluminium bandles, ISI marked, anodised (anodic coating not less than grade AC IO as per IS : 1868)       teach       6         9       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections / approvidar Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EDDM rubber/ neoprene gasket etc. Aluminium sections       shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium smodic coating of grade AC IS)       , or fixed portion         Anodised aluminium (anodised transparent or dyed to required transparent or dyed to required transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC IS)       , or fixed portion         .       .       .       .       .       .         . <td></td> <td></td> <td></td> <td></td>				
Pre-laminated particle board with decorative lamination on both sides       sqm       24         S.       Repairing and remaking Armstrong existing false celling including necessary material (Fastener, main and runner etc., new tile will be paid extra as per Item.).       sqm       32         6.       Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.       a       3         7.       Providing and fixing pulley roller set for sliding door (two Each est)       Each est       6         (B) Name of the work-Partition work in Cell culture repository(museum G F) at NBFGR campus       Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :       acch 6         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :       -         - For fixed portion       Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)       -       For fixed portion         - For shutt				
sides       sides         5.       Repairing and remaking Armstrong existing false celling including necessary material (Fastener, main and runner etc., new tile will be paid extra as per Item.).       sqm       32         6.       Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.       ach       3         7.       Providing and fixing pulley roller       set for sliding door (two set       Each       6         9       Providing and fixing aluminium handles. ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :       i.25         12.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections       shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / pancling. C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including				
5.       Repairing and remaking Armstrong existing false celling including necessary material (Fastener, main and runner etc., new tile will be paid extra as per Item.).       sqm       32         6.       Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.       a       3         7.       Providing and fixing pulley roller set for sliding door (two pulley/roller in each set)       set       6         (B) Name of the work-Partition work in Cell culture repository(museum G F) at NBFOR campus       a       6         1.       Providing and fixing aluminium handles. ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :       each       6         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections       shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling. C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and fasteners to be paid for separately) : - For fixed portion       kg       1         Anodised alumin		-	sqm	24
necessary material (Fastener, main and runner etc., new tile will be paid extra as per Item.).         image: complete:           6.         Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.         each 3           7.         Providing and fixing pulley roller set for sliding door (two pulle//roller in each set)         Each 6           (B) Name of the work-Partition work in Cell culture repository(museum G F) at NBFGR campus         each 6           1.         Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) (transparent or dyed to required colour or shade, with necessary screws etc. complete :         125 mm           2.         Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections         each 6           2.         Providing and fixing aluminum sections         shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :                 - For fixed portion         kg         1           Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of p				
paid extra as per Item.).         paid extra as per Item.).           6.         Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.         3           7.         Providing and fixing pulley roller set for sliding door (two Each 6 pulley/roller in each set)         Each 6           (B) Name of the work-Partition work in Cell culture repository(museum G F) at NBFGR campus         Each 6           1.         Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :         125 mm           2.         Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections           shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately): - For fixed portion         kg         1           Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated alumini	5.		sqm	32
6.       Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.       acach       3         7.       Providing and fixing pulley roller set for sliding door (two pulle//roller in each set)       Each       6         (B) Name of the work-Partition work in Cell culture repository(museum G F) at NBFGR campus       Providing and fixing aluminium handles, ISI marked, anodised       6         (anodic coating not less than grade AC 10 as per IS : 1868)       transparent or dyed to required colour or shade, with necessary screws etc. complete :       each       6         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sctions       shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling. C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :       , For fixed portion         Anodised aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15)       g       375         .       Powder coated aluminium (minimum thickness of powder coating shad a				
quality) for aluminum doors including necessary cutting and making good etc. complete.       3         7.       Providing and fixing pulley roller set for sliding door (two pulley/roller in each set)       Each set       6         (B) Name of the work-Partition work in Cell culture repository(museum G F) at NBFGR campus       Each (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :       2         125 mm       each       6         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections         shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15)       kg       1         Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15)       kg       1         Powder coated aluminium (modised transparent or dyed to required shade according to IS: 1				
making good etc. complete.           7.         Providing and fixing pulley roller set for sliding door (two Each 6 pulley/roller in each set)           (B) Name of the work-Partition work in Cell culture repository(museum G F) at NBFGR campus           1.         Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per 1S: 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :           1.1         Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dina dn size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections           shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately):         - For fixed portion           Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)         kg         1           Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15)         kg         1           Anodised aluminium (nodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of	6.			
7.       Providing and fixing pulley roller set for sliding door (two pulley/roller in each set)       Each set       6         (B) Name of the work-Partition work in Cell culture repository(museum G F) at NBFGR campus       Image: Compute Computeres Computeres Computeres Compute Computeres Compute Compute Compu			each	3
pulley/roller in each set)         set           (B) Name of the work-Partition work in Cell culture repository(museum G F) at NBFGR campus         campus           1.         Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :         each 6           2.         Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required di and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium scitons shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion         kg         1           Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & wentilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)         Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & wentilators including providing and fixing hingues/ p				
(B) Name of the work-Partition work in Cell culture repository(museum G F) at NBFGR campus         1.       Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :       each       6         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sactions       each       6         2.       providing and fixing aluminium more clean and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sclean set of reguired and minium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)       For fixed portion       Anodised aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15)       kg       1         1.5)       Powder coated aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)       kg       1         1.5)       Powder coated aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade A	7.	Providing and fixing pulley roller set for sliding door (two	Each	6
1.       Providing and fixing aluminium hanles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :       125 mm         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC for 15) Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC for - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required (Fittings shall be paid for separately) Anodised aluminium (moinimum thickness of powder coating 50 micron)       Kg       15         3.       Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket ret. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item); With float glass panes of 5.50 mm		pulley/roller in each set)	set	
1.       Providing and fixing aluminium handles, ISI marked, anodised (anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete :       125 mm       each       6         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)r/tr>       kg375        Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15)kg375        .For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)kg<	<b>(B</b> )	Name of the work-Partition work in Cell culture repository(museum C	G F) at NI	BFGR
(anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary screws etc. complete : 125 mmeach2.Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provison for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required aluminium (minimum thickness of powder coating 50 micron)Kg3753.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of gangener-in-charge.(Cost of aluminium snap beading for grade AC 15)Kg1		1		
transparent or dyed to required colour or shade, with necessary screws etc. complete : 125 mmeach62.Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating shade according to IS: 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (minimum thickness of powder coating 50 micron)kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item); With Hoat glass panes of 5.50 mm thicknesssqm <td>1.</td> <td></td> <td></td> <td></td>	1.			
screws etc. complete :       each       6         125 mm       each       6         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections       shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately):       -         - For fixed portion       Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)       kg       375         - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provisori for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)       Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)       kg       1         5)       Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15)       kg       1         5)       Powder coated aluminium (minimum thickness of powder c				
125 mm       each       6         2.       Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections       shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :       For fixed portion         Anodised aluminium (modised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)       kg       375         9 Owder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15)       kg       1         15)       Powder coated aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)       kg       375         3.       Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge. (Cost of aluminium snap beading shall be paid in basic item);       sqm       58				
<ul> <li>Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections</li> <li>shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :</li> <li>For fixed portion</li> <li>Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)</li> <li>For shutters of doors, windows &amp; ventilators including provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)</li> <li>Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)</li> <li>For shutters of doors, windows &amp; ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)</li> <li>Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)</li> <li>Powder coated aluminium (minimum thickness of powder coating 50 micron)</li> <li>Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium</li></ul>		1		
<ul> <li>ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) :</li></ul>		125 mm	each	6
sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm58	2.			
make conforming to IS: 733 and IS: 1285, fixing with dash fasteners of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (minimum thickness of powder coating 50 micron)kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm58				
of required dia and size, including necessary filling up the gaps at junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)Kg753.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thickness58				
junctions, i.e. at top, bottom and sides with required EPDM rubber/ neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron) 3. Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thickness 4. Providing and fixing 10 mm thick prelaminated particle board flat				
neoprene gasket etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)kg1Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (minimum thickness of powder coating 50 micron)kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm58				
shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)kg3753.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm58				
wherever required including cleat angle, Aluminium snap beading for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)kg3753.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm58				
for glazing / paneling, C.P. brass / stainless steel screws, all complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)kgPowder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm58				
complete as per architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)kg1Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flat50				
architectural drawings and the directions of Engineer-in-charge. (Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)kg1Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm58				
(Glazing, paneling and dash fasteners to be paid for separately) : - For fixed portion Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)Kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm58				
<ul> <li>For fixed portion         <ul> <li>Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)</li> <li>Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15)</li> <li>For shutters of doors, windows &amp; ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately)             <ul> <li>Anodised aluminium (minimum thickness of powder coating of grade AC 15)</li> <li>For shutters of IS: 1868, Minimum anodic coating of grade AC 15)</li> <li>Powder coated aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)</li> <li>Powder coated aluminium (minimum thickness of powder coating 50 micron)</li> </ul> </li> <li>3. Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item):</li></ul></li></ul>				
Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)kgPowder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flat5050				
shade according to IS: 1868, Minimum anodic coating of grade AC 15)kg1Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)Kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flatFor the second state of t				
15) Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flatstatestate				
Powder coated aluminium (minimum thickness of powder coating 50 micron): 1868, Minimum anodic coating of grade AC 15) - For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)kg3753.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flat			kg	1
50 micron): 1868, Minimum anodic coating of grade AC 15)kg375- For shutters of doors, windows & ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)kg1Powder coated aluminium (minimum thickness of powder coating 50 micron)Kg753.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flat575				
<ul> <li>For shutters of doors, windows &amp; ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)</li> <li>Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thickness</li> <li>Providing and fixing 10 mm thick prelaminated particle board flat</li> </ul>				~
and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flatFitting shall be paid for separately			kg	375
wherever required including the cost of EPDM rubber / neoprene gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 				
gasket required (Fittings shall be paid for separately) Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15) Powder coated aluminium (minimum thickness of powder coating 50 micron)kg13.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flatFourthead flatFourthead flat				
Anodised aluminium (anodised transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade AC 15)kg1Powder coated aluminium (minimum thickness of powder coating 50 micron)Kg753.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flat				
shade according to IS: 1868, Minimum anodic coating of grade AC 15)kg1Powder coated aluminium (minimum thickness of powder coating 50 micron)Kg753.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flatFourthead and flatFourthead and flat				
15) Powder coated aluminium (minimum thickness of powder coating 50 micron)Kg753.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flat			1	
Powder coated aluminium (minimum thickness of powder coating 50 micron)Kg753.Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flat			kg	1
50 micron)       50 micron)         3.       Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item):         With float glass panes of 5.50 mm thickness       sqm         4.       Providing and fixing 10 mm thick prelaminated particle board flat				
<ul> <li>Providing and fixing glazing in aluminium door, window, ventilator shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item):</li> <li>With float glass panes of 5.50 mm thickness sqm 58</li> <li>4. Providing and fixing 10 mm thick prelaminated particle board flat</li> </ul>			Kg	75
shutters and partitions etc. with EPDM rubber / neoprene gasket etc. complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flat	2			
complete as per the architectural drawings and the directions of engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item): With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flat	3.			
engineer-in-charge.(Cost of aluminium snap beading shall be paid in basic item):sqmWith float glass panes of 5.50 mm thicknesssqm4.Providing and fixing 10 mm thick prelaminated particle board flat				
basic item):     sqm     58       With float glass panes of 5.50 mm thickness     sqm     58       4.     Providing and fixing 10 mm thick prelaminated particle board flat     58				
With float glass panes of 5.50 mm thicknesssqm584.Providing and fixing 10 mm thick prelaminated particle board flat				
4. Providing and fixing 10 mm thick prelaminated particle board flat				50
	4		sqm	58
pressed three layer or graded wood particle board conforming to	4.			
		pressed three layer or graded wood particle board conforming to		

	IS:12823 Grade 1 Type II, in panelling fixed in aluminum doors,		
	windows shutters and partition frames with C.P. brass / stainless		
	steel screws etc. complete as per architectural drawings and	sqm	16
	directions of engineer-in-charge.		
	Pre-laminated particle board with decorative lamination on both		
~	sides		21
5.	Repairing and remaking Armstrong existing false celling including	sqm	21
	necessary material (Fastener, main and runner etc ,new tile will be		
6	paid extra as per Item.).		
6.	Providing and fixing 100mm brass locks (best make of approved	1	2
	quality) for aluminium doors including necessary cutting and	each	3
7	making good etc. complete.	East	6
7.	Providing and fixing pulley roller set for sliding door (two pulley/roller in each set)	Each	6
(C	) Name of the work-Partition work in Microbial repository( museum C	set	PECD
(C		F) at M	DFUK
1.	campus Providing and fixing aluminium handles, ISI marked, anodised		
1.			
	(anodic coating not less than grade AC 10 as per IS : 1868) transparent or dyed to required colour or shade, with necessary		
	screws etc. complete :		
	125 mm	each	14
2.	Providing and fixing aluminium work for doors, windows,	cucii	17
2.	ventilators and partitions with extruded built up standard tubular		
	sections/ appropriate Z sections and other sections of approved		
	make conforming to IS: 733 and IS: 1285, fixing with dash fasteners		
	of required dia and size, including necessary filling up the gaps at		
	junctions, i.e. at top, bottom and sides with required EPDM rubber/		
	neoprene gasket etc. Aluminium sections		
	shall be smooth, rust free, straight, mitred and jointed mechanically		
	wherever required including cleat angle, Aluminium snap beading		
	for glazing / paneling, C.P. brass / stainless steel screws, all		
	complete as per		
	architectural drawings and the directions of Engineer-in-charge.		
	(Glazing, paneling and dash fasteners to be paid for separately) :		
	- For fixed portion		
	Anodised aluminium (anodised transparent or dyed to required		
	shade according to IS: 1868, Minimum anodic coating of grade AC	kg	1
	15)	0	
	Powder coated aluminium (minimum thickness of powder coating		
	50 micron): 1868, Minimum anodic coating of grade AC 15)	kg	628
	- For shutters of doors, windows & ventilators including providing	J	
	and fixing hinges/ pivots and making provision for fixing of fittings		
	wherever required including the cost of EPDM rubber / neoprene		
	gasket required (Fittings shall be paid for separately)		
	Anodised aluminium (anodised transparent or dyed to required		
	shade according to IS: 1868, Minimum anodic coating of grade AC	kg	1
	15)	-	
	Powder coated aluminium (minimum thickness of powder coating	Kg	140
	50 micron)		
3.	Providing and fixing glazing in aluminium door, window, ventilator		
	shutters and partitions etc. with EPDM rubber / neoprene gasket etc.		
	complete as per the architectural drawings and the directions of		
	engineer-in-charge.(Cost of aluminium snap beading shall be paid in		
	basic item):		
	With float glass panes of 5.50 mm thickness	sqm	100
4.	Providing and fixing 10 mm thick prelaminated particle board flat		
	pressed three layer or graded wood particle board conforming to		
	IS:12823 Grade 1 Type II, in panelling fixed in aluminum doors,		
	windows shutters and partition frames with C.P. brass / stainless		
	steel screws etc. complete as per architectural drawings and		

	directions of engineer-in-charge. Pre-laminated particle board with decorative lamination on both sides	Sqm	28
5.	Repairing and remaking Armstrong existing false celling including necessary material (Fastener, main and runner etc ,new tile will be paid extra as per Item.).	sqm	35
6.	Providing and fixing 100mm brass locks (best make of approved quality) for aluminium doors including necessary cutting and making good etc. complete.	each	3
7.	Providing and fixing pulley roller set for sliding door (two pulley/roller in each set)	Each set	14

Mark (YES) if specification offered is as per tender or better. If not, specify the specification offered. An item-by-item commentary on the purchaser's Technical Specifications demonstrating substantial responsiveness of the goods and services to those specifications or a statement of deviations and exceptions to the provision of the Technical Specifications.

 Published/Printed Technical literature/brochures/manuals should be attached along with this format that certifies the quoted specification. Simple internet downloaded are not accepted unless the catalogue/brochures from authorized website of original manufacturer can be certified.
 Compliance/Deviation statement comparing the specification of the quoted model to the required specifications. This statement should also give the last page of the technical literature where the relevant specification is mentioned.
 Failure to give support documents for verifying specification will lead to rejection of bid.

#### SIGNATURE WITH STAMP OF THE BIDER